



Dongguan GongFu Electronics Co.Ltd. GFEFUSE® Focus: fuse holder and fuse

5H20L Series DC automobile fuse

1. Purpose and use

This series of fuses are suitable for rated DC voltage up to 500V (450V), In the line with rated current up to 150A, the breaking capacity is 50kA, which is the comprehensive protection of on-board battery, on-board line system and inverter. At the same time, it has the characteristics of strong current limiting capacity, high breaking capacity, fast short-circuit breaking speed, and it can withstand temperature shock, mechanical vibration shock, current shock, chemical load, etc. This series of products conforms to ISO 8820 and JASO D622 and GB / T31465. Applicable standards for environmental reliability: GB/T31465.6, ISO 8820-8, JASO D622, UL248-20

2. Normal working conditions

Normal operating conditions of ambient air temperature: - 5 °C ~ 40 °C; allowable operating conditions: - 40 °C ~ + 125 °C;

3. Use category

Full range fast fuse

4. Structural characteristics

The melting tube of the product is made of high-temperature resistant ceramic material, with high flame-retardant performance and strong hardness.

The melt is sealed in the melting tube with a variable cross-section melt made of 99.99% pure silver. The melting tube is filled with chemically treated high-purity quartz sand and specially treated chemical materials as arc extinguishing medium. The contact surface is

TEL:0769-82391938

FAX:0769-82391939

<http://www.dcfuselink.com>



Dongguan GongFu Electronics Co.Ltd. GFEFUSE® Focus: fuse holder and fuse

silver plated to ensure reliable electrical performance, greatly reducing temperature rise and power consumption; Both ends of the melt are firmly connected with the contact by spot welding, which greatly enhances the safety and reliability of breaking short circuit fault current

5.Agreed current and agreed time

Test current A	Fusing time s			
	In: <60A		In: ≥60A	
	min	max	min	max
1.1In	14400	—	14400	—
1.35In	150	3600	150	3600
1.5In	—	—	20	1500
2In	0.5	100	1	300
3In	0.1	15	0.2	30
5In	0.05	1	0.05	1

Note: the agreed current and agreed time required by the customer can be negotiated with our company.

The characteristics of fuse will vary according to the use environment and surrounding design requirements. The performance characteristics are obtained according to the rated constant temperature of 25 °C



Dongguan GongFu Electronics Co.Ltd. GFEFUSE® Focus: fuse holder and fuse

6. Main parameters

NO:	Product model	Rated current			Breaking Capacity (KA)
		(A)	Rated voltage DC (V)	Maximum voltage drop (mV)	
1	5H20L025	25	500V/450V	200	50
2	5H20L030	30	500V/450V	200	50
3	5H20L040	40	500V/450V	200	50
4	5H20L050	50	500V/450V	200	50
5	5H20L060	60	500V/450V	200	50
6	5H20L070	70	500V/450V	200	50
7	5H20L080	80	500V/450V	200	50
8	5H20L100	100	500V/450V	200	50
9	5H20L125	125	500V/450V	200	50
10	5H20L150	150	500V/450V	200	50

TEL:0769-82391938


FAX:0769-82391939

<http://www.dcfuselink.com>



Dongguan GongFu Electronics Co.Ltd. GFEFUSE® Focus: fuse holder and fuse

7. Product scale:



TEL:0769-82391938


FAX:0769-82391939

<http://www.dcfuselink.com>



Dongguan GongFu Electronics Co.Ltd. GFEFUSE® Focus: fuse holder and fuse

8. Characteristic curve:(For reference)



TEL:0769-82391938

FAX:0769-82391939

<http://www.dcfuselink.com>